



strands®


-lighting division




Part No. 908536
PRESIDENT 25W CLEAR LENS



Part No. 908537
PRESIDENT 25W AMBER POSITION LIGHT CLEAR LENS



Part No. 908538
PRESIDENT 25W RED POSITION LIGHT CLEAR LENS



Part No. 908539
PRESIDENT 51W CLEAR LENS

PRESIDENT WORK LIGHT LED



PART NO.	908536	908537	908538	908539
VOLTAGE	12-70V DC	12-70V DC	12-70V DC	12-70V DC
CONSUMPTION	25W	25W	25W	51W
THEORETICAL LUMEN	3398	3398	3398	6637
ACTUAL LUMEN	3210	3210	3210	6320
1 LUX @	72 m	72 m	72 m	98 m
IP-CLASS	IP6K9K	IP6K9K	IP6K9K	IP6K9K
BEAM PATTERN	Flood	Flood	Flood	Flood
COLOR TEMPERATURE	5700K	5700K	5700K	5700K
POSITION LIGHT	No	Amber	Red	No
CONNECTION	Cable	Cable	Cable	Cable
CABLE LENGTH	2000 mm	2000 mm	2000 mm	2000 mm
MATERIAL HOUSING	Aluminium	Aluminium	Aluminium	Aluminium
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
LENGTH	109 mm	109 mm	109 mm	109 mm
HEIGHT	109 mm	109 mm	109 mm	109 mm
DEPTH	49 mm	49 mm	49 mm	70 mm
HEIGHT INCLUDING BRACKET	133 mm	133 mm	133 mm	133 mm
OPERATING TEMPERATURE	-40°C · +40°C	-40°C · +40°C	-40°C · +40°C	-40°C · +40°C
ADR-APPROVED	Yes	Yes	Yes	Yes
E-APPROVED	No	No	No	No
EMC-CERTIFICATE	ECE R10	ECE R10	ECE R10	ECE R10